

1 CLAIMS

2  
3 I Claim:

4  
5 1. A molding remover system, comprising:  
6 a handle; and  
7 a shaft member extending from said handle, wherein said shaft member  
8 includes a distal portion that is angled toward said handle and wherein said distal  
9 portion includes an engaging portion for selectively engaging a retainer clip.  
10

11  
12 2. The molding remover system of Claim 1, wherein said shaft member is  
13 comprised of:  
14 a first segment extending from said handle;  
15 a second segment extending from said first segment at a first angle; and  
16 a third segment extending from said second segment at a second angle, wherein  
17 said engaging portion extends from said third segment at a third angle.  
18

19  
20 3. The molding remover system of Claim 2, wherein said first angle is  
21 comprised of an angle greater than one hundred degrees.  
22

23  
24 4. The molding remover system of Claim 2, wherein said second angle is  
25 comprised of an angle greater than one hundred degrees.  
26

27  
28 5. The molding remover system of Claim 2, wherein said third angle is  
29 comprised of an angle less than ninety degrees.

1  
2  
3           6. The molding remover system of Claim 2, wherein said engaging portion is  
4 substantially parallel to said first segment.  
5

6  
7           7. The molding remover system of Claim 1, wherein said engaging portion is  
8 directed towards said handle.  
9

10  
11           8. The molding remover system of Claim 1, wherein said engaging portion is  
12 tapered.  
13

14  
15           9. The molding remover system of Claim 1, wherein said engaging portion is  
16 flat.  
17

18  
19           10. The molding remover system of Claim 9, wherein said engaging portion  
20 has a broad structure.  
21

22  
23           11. The molding remover system of Claim 1, wherein said shaft member is  
24 comprised of:

25           an extended portion extending from said handle;  
26           a first segment extending from said extended portion;  
27           a second segment extending from said first segment at a first angle; and  
28           a third segment extending from said second segment at a second angle, wherein  
29 said engaging portion extends from said third segment at a third angle.

1  
2  
3           12. The molding remover system of Claim 11, wherein said first angle is  
4 comprised of an angle greater than one hundred degrees.  
5  
6

7           13. The molding remover system of Claim 11, wherein said second angle is  
8 comprised of approximately ninety degrees.  
9  
10

11           14. The molding remover system of Claim 11, wherein said third angle is  
12 comprised of approximately ninety degrees.  
13  
14

15           15. The molding remover system of Claim 11, wherein said engaging portion is  
16 substantially parallel to said first segment.  
17  
18

19           16. The molding remover system of Claim 11, wherein said engaging portion is  
20 directed towards said handle.  
21  
22

23           17. The molding remover system of Claim 11, wherein said engaging portion is  
24 tapered.  
25  
26

27           18. The molding remover system of Claim 11, wherein said engaging portion is  
28 flat.  
29

1  
2           19. The molding remover system of Claim 18, wherein said engaging portion  
3 has a broad structure.  
4

5  
6           20. A molding remover system, comprising:  
7           a handle; and  
8           a shaft member extending from said handle, wherein said shaft member  
9 includes a distal portion that is angled toward said handle and wherein said distal  
10 portion includes an engaging portion for selectively engaging a retainer clip;

11           wherein said shaft member is comprised of:  
12                 a first segment extending from said handle;  
13                 a second segment extending from said first segment at a first angle; and  
14                 a third segment extending from said second segment at a second angle,  
15           wherein said engaging portion extends from said third segment at a third angle;  
16           wherein said first angle is comprised of an angle greater than one hundred  
17 degrees;

18           wherein said second angle is comprised of an angle greater than one hundred  
19 degrees;

20           wherein said third angle is comprised of an angle less than ninety degrees;  
21           wherein said engaging portion is substantially parallel to said first segment;  
22           wherein said engaging portion is directed towards said handle;  
23           wherein said engaging portion is flat and tapered;  
24           wherein said engaging portion has a broad structure.  
25